

.....

Warrior Products, Inc.

SAFARI FRONT LIGHT BAR INSTALLATION INSTRUCTIONS

WAR 844/872

'87 - '96 Wrangler/ '97 & Up TJ

Read all instructions before proceeding.

Due to welding, handling, shipping, etc., the legs may need to be “tweaked” slightly (bent in or out) to fit correctly. A small amount of twisting will not hurt the bar. Be careful not to scratch the paint as you install the legs.

NOTE: The nut plates on some Jeep windshields may come loose when both bolts are removed at the same time. Loosen both bolts, remove one, install bracket with one bolt, spin out of the way and remove other bolt. Try to keep one bolt engaged through the windshield at all times.

1. Remove the 2 screws on the upper outboard side of the drivers side windshield hinge. Repeat for the passenger side hinge as well. New screws are provided.
2. Assemble the Light Bar by inserting windshield mounting brackets onto the short light bar hoop and inserting snapper pins to hold in place. The light tabs should be facing forward and the windshield mounting brackets towards the rear of the vehicle.
3. Place the front Light Bar assembly onto the windshield. Install screws through the Light Bar mounting brackets.
4. Lights should be installed per the manufacturer’s instructions.

Enjoy your new Safari Light Bar by Warrior Products!

.....

“Your Knight in Shining Armor!”