

# LIGHTING

## SERVICE DATA

Headlight relay	3 - 5: 10 k $\Omega$ or higher 3 - 5: Below 1 $\Omega$ (Battery voltage applied to terminals 1 and 2)
Headlight dimmer relay	3 - 4: Below 1 $\Omega$ 3 - 4: 10 k $\Omega$ or higher (Battery voltage applied to terminals 1 and 2) 3 - 5: 10 k $\Omega$ or higher 3 - 5: Below 1 $\Omega$ (Battery voltage applied to terminals 1 and 2)
Taillight relay	3 - 5: 10 k $\Omega$ or higher 3 - 5: Below 1 $\Omega$ (Battery voltage applied to terminals 1 and 2)

SS

## TORQUE SPECIFICATIONS

Part Tightened	N*m	kgf*cm	ft.*lbf
Headlight assembly x Front combination light assembly	5.4	55	48 in.*lbf
Rear combination light assembly x Body	6.0	61	53 in.*lbf
Front door courtesy switch x Access door	7.0	71	62 in.*lbf
Access panel upper lock assembly x Access door	12	122	9
Access panel lower lock assembly x Access door	5.0	51	44 in.*lbf
Back door courtesy switch x Body	7.0	71	62 in.*lbf
Negative battery terminal x Battery	3.9	40	35 in.*lbf

**SS**