

PARKING BRAKE**SERVICE DATA**

| | | |
|--|-----------------------|---|
| Parking brake lever travel at 200 N (20 kgf, 45 lbf) | | 5 to 7 clicks |
| Brake disc inside diameter | Standard Maximum | 210 mm (8.268 in.) 211 mm (8.307 in.) |
| Parking brake shoe lining thickness | Standard Minimum | 4.0 mm (0.157 in.) 1.0 mm (0.039 in.) |
| Parking brake shoe lever clearance | | Less than 0.25 mm (0.0098 in.) |
| Parking brake switch | Released Pushed in | Below 1 Ω 10 k Ω or higher |

SS

TORQUE SPECIFICATIONS

| Part Tightened | N*m | kgf*cm | ft.*lbf |
|---|-----|--------|------------|
| Rear wheel | 112 | 1,137 | 82 |
| Parking brake lever x Body | 13 | 127 | 9 |
| Battery negative terminal x Battery | 3.9 | 40 | 35 in.*lbf |
| Parking brake cable x Frame assembly | 13 | 127 | 9 |
| Parking brake cable x Parking brake plate | 8.0 | 82 | 71 in.*lbf |
| Parking brake cable heat insulator x Frame assembly | 13 | 127 | 9 |
| Rear disc brake caliper assembly x Rear axle housing assembly | 105 | 1,071 | 78 |

SS